1. IDENTIFICATION

Product Identifier: W-75 SPEED STRIPPER Date of Revision: April 23, 2024

Product Code: J461

Other Name(s): not applicable
Distributed By: not applicable

Recommended Use and Restrictions on Use: floor stripper

Manufactured By: Ostrem Chemical Co. Ltd. Phone/Emergency Phone:

2310 - 80th Avenue NW 780-440-1911

Edmonton, Alberta, Canada T6P 1N2 Mon. - Fri. 8:00am - 4:30pm MT

www.ostrem.com

2. HAZARDS IDENTIFICATION

Classification of the Mixture: Carcinogenicity - Category 2

Serious Eye Damage/Irritation - Category 1

Flammable Liquids - Category 4 Skin Corrosion/Irritation - Category 1

Label Elements:

Hazard Pictogram(s):





Signal Word: DANGER

Hazard Statement(s): Suspected of causing cancer.

Causes serious eye damage.

Combustible liquid.

Causes severe skin burns and eye damage.

Precautionary Statement(s):

Prevention: Do not breathe dusts or mists.

Wash hands thoroughly after handling. Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves, protective clothing, and eye/face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a poison centre or

physician.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash

contaminated clothing before reuse. Immediately call a poison centre or physician.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a

poison centre or physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present

and easy to do. Continue rinsing. Immediately call a poison centre or physician.

If exposed or concerned: Get medical advice.

Storage: Store locked up.

Store in a well-ventilated place.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

Physical/health hazards not otherwise classified:

not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u> <u>Conc. w/w</u> <u>CAS #</u> <u>Common Names</u>

W-75 SPEED STRIPPER Page 1 of 5

ethylene glycol monobutyl ether sodium hydroxide (50%)	3 - 7% 5 - 10%	111-76-2 1310-73-2	2-butoxy ethanol, glycol ether EB caustic soda, lye
monoethanolamine	7 - 13%	141-43-5	
trisodium nitrilotriacetate	1 - 5%	5064-31-3	NTA
glycol ether DB	5 - 10%	112-34-5	

4. FIRST-AID MEASURES

Necessary Measures:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a poison centre or physician.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. Immediately call a poison centre or physician.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison centre or physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do.

Continue rinsing. Immediately call a poison centre or physician.

If exposed or concerned: Get medical advice.

Most important symptoms, both acute and delayed:

Suspected of causing cancer.

Causes serious eve damage.

Causes severe skin burns and eye damage.

Indication of immediate medical attention and special treatment needed, if necessary:

not applicable

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media:

Use extinguishing media appropriate for surrounding fire.

Specific hazards arising from the chemical (e.g.: hazardous combustion products):

May liberate carbon monoxide, carbon dioxide and oxides of sodium.

Special protective equipment and precautions for firefighters:

As for surrounding fire. Firefighters should wear full protective clothing and self contained breathing equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear appropriate protective equipment. See section 8.

Environmental precautions:

Prevent from entering sewers, waterways or low areas.

Methods and materials for containment and cleaning up:

Isolate hazard area and restrict access. Small spills: soak up with inert absorbent material and scoop into containers. Large spills: prevent contamination of waterways. Dike and pump into suitable containers. Clean up residual with absorbent material, place in appropriate container and flush with water.

7. HANDLING AND STORAGE

Precautions for safe handling:

Do not breathe dusts or mists.

Wash hands thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not ingest. Avoid contact with eyes, skin and clothing.

Conditions for safe storage, including any incompatibilities:

Store locked up.

Store locked up.

Store in a well-ventilated place.

Keep out of reach of children. Store in a cool, dry area.

W-75 SPEED STRIPPER Page 2 of 5

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters - Exposure limits:

Ingredient: Limit:

ethylene glycol monobutyl ether ACGIH TWA: 20 ppm sodium hydroxide (50%) ACGIH TLV: 2 mg/m3 monoethanolamine ACGIH TWA: 6 ppm ACGIH STEL: 6 ppm

trisodium nitrilotriacetate not available glycol ether DB not available

Appropriate engineering controls:

Provide exhaust ventilation to keep airborne levels below recommended exposure limits.

Respiratory protection:

If exposure exceeds occupational exposure limits, use an appropriate NIOSH approved respirator.

Other protection:

Wear protective gloves, protective clothing, and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, colour etc.):clear red liquidOdour:butyl odourOdour threshold:not availablepH:12.2

Melting/Freezing point:not availableInitial boiling point and range:not availableFlash point:65 C

not available **Evaporation rate:** Flammability (solid, gas): not available not available Upper/lower flammability or explosive limits: Vapour pressure: not available not available Vapour density: Relative density (specific gravity): 1.050 complete Solubility(ies): Partition co-efficient: n-octanol/water: not available not available Auto-ignition temperature:

Auto-ignition temperature:not availableDecomposition temperature:not availableViscosity:not available

10. STABILITY AND REACTIVITY

Reactivity:

This material is considered to be non-reactive under normal use conditions.

Chemical stability:

Stable.

Possibility of hazardous reactions:

Reacts with acids and metals

Conditions to avoid (e.g.: static discharge, shock or vibration):

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials:

Oxidizers / Acid

Hazardous decomposition products:

not available

11. TOXICOLOGICAL INFORMATION

POTENTIAL ACUTE HEALTH EFFECTS

Inhalation: May cause respiratory tract irritation.

W-75 SPEED STRIPPER Page 3 of 5

Ingestion: May be harmful if swallowed. Eye contact: Causes serious eye damage.

Skin contact: Causes severe skin burns and eye damage.

Skin absorption: not available

POTENTIAL CHRONIC HEALTH EFFECTS

Inhalation:not availableIngestion:not availableEye contact:not availableSkin contact:not availableSkin absorption:not available

Mutagenicity: not available

Carcinogenicity:

Reproductive toxicity:

Sensitization of product:

Specific Target Organ Toxicity - repeated exposure:

This information, if applicable, can be found in Section 2.

This information, if applicable, can be found in Section 2.

This information, if applicable, can be found in Section 2.

This information, if applicable, can be found in Section 2.

This information, if applicable, can be found in Section 2.

This information, if applicable, can be found in Section 2.

Toxicological Data:

<u>Ingredient:</u> <u>Data:</u>

ethylene glycol monobutyl ether Oral LD50: 745 mg/kg (rat)

Dermal LD50: 1250 mg/kg (rat)

sodium hydroxide (50%) not available

monoethanolamine Oral LD50: 1089 mg/kg (rat) trisodium nitrilotriacetate Oral LD50: 1450 mg/kg (rat)

glycol ether DB not available

Other Toxicological Information on Ingredients:

12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial, where available):

Persistence and degradability:

Bioaccumulative potential:

Mobility in soil:

Other adverse effects:

not available

not available

not available

not available

13. DISPOSAL CONSIDERATIONS

Waste disposal: Disposal of all waste must be done according to local, provincial and federal regulations.

14. TRANSPORT INFORMATION

TDG classification: UN 1760; CORROSIVE LIQUID, N.O.S. (SODIUM HYDROXIDE, ETHANOLAMINE); CLASS 8;

PG II

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. PREPARATION INFORMATION

Prepared by: Technical Services Department, Ostrem Chemical Co. Ltd., Ph.: 780-440-1911

Date of Preparation: March 09, 2023

Date of Revision: April 23, 2024

This Safety Data Sheet may not be changed or altered in any way without the express knowledge and permission of Ostrem Chemical Co. Ltd.

W-75 SPEED STRIPPER Page 4 of 5

End of Document

W-75 SPEED STRIPPER Page 5 of 5